




Kofler Unterflurhydranten / Idranti sottosuolo Kofler

	<p>UNTERFLUR - ZWEIBEINHYDRANT zu 1 ¼“ mit Alu-Kupplung und gebogen zu 1 ¼“</p> <p>IDRANTE SOTTOSUOLO A DUE PIEDI zinc. da 1 ¼“ con giunto in alluminio e curvato da 1 ¼“</p> <hr/> <p>UNTERFLUR - ZWEIBEINHYDRANT zu 1 ½“ mit Alu-Kupplung und gebogen zu 1 ½“</p> <p>IDRANTE SOTTOSUOLO A DUE PIEDI zinc. da 1 ½“ con giunto in alluminio e curvato da 1 ½“</p> <hr/> <p>UNTERFLUR - ZWEIBEINHYDRANT zu 2“ mit Alu-Kupplung und gebogen zu 2“</p> <p>IDRANTE SOTTOSUOLO A DUE PIEDI zinc. da 2“ con giunto in alluminio e curvato da 2“</p>
	<p>PFROPFEN verz. für Unterflur-Zweibeinhydrant zu 1 ½“</p> <p>TAPPO zinc. per idrante sottosuolo da 1 ½“</p>
	<p>STANDROHR VERZINKT mit Schelle für Unterflur-Zweibeinhydrant</p> <p>ASTA ZINCATA con fascetta per idrante sottosuolo</p> <p>1“ zu 1 Meter Länge – da 1 ml. 1 ¼“ zu 1 Meter Länge – da 1 ml. 1 ½“ zu 1 Meter Länge – da ml. 1“ zu 1,5 Meter Länge – da 1,5 ml. 1 ¼“ zu 1,5 Meter Länge – da 1,5 ml. 1 ½“ zu 1,5 Meter Länge – da 1,5 ml.</p>